

Durata®

Optim Insulation, Endocardial, Steroid-Eluting Defibrillation Leads

MODELS 7120, 7121, 7122, 7130, 7131, 7170, 7171



SPECIFICATIONS

- **Designed for Reliability with Redundant Conductors**
 - Durata® defibrillation leads offer the safety of a built-in backup system by incorporating the use of redundant conductors in their design. These additional conductors serve as backup in the unlikely event of a conductor failure.
- **Symmetrical Lead Body with Oversized Lumens**
 - The symmetrically aligned cables within the lead body, as well as a centrally located coil, provide for additional protection to the inner coil. Oversized lumens for cables allow effective absorption of external forces, e.g., clavicular crush.
- **Optim® Lead Insulation**
 - Optim insulation is a hybrid insulation material, the first-of-its-kind developed specifically for cardiac lead use, that blends the biostability and flexibility of high-performance silicone rubber with the strength, tear resistance and abrasion resistance of polyurethane.
- **Designed to Prevent Tissue Ingrowth**
 - The Durata defibrillation lead combines two innovative designs intended to help prevent tissue ingrowth. The lead uses a flat outer wire, providing a low profile for its defibrillation coils. In addition, the lead is backfilled with silicone to completely fill the shock coil space.
- **Lower Thresholds with Steroid Elution**
 - The Durata defibrillation lead is a steroid-eluting lead that uses a monolithic controlled release device (MCRD) as a vehicle for steroid delivery. The dexamethasone sodium phosphate in a silicone matrix is designed to reduce inflammation at the lead-tissue interface resulting in lower acute and chronic stimulation thresholds.
- **Thinner than Any Competitive Lead on the Market**
 - The Durata lead is thinner than any competitive lead on the market. The small diameter Durata lead has a number of design characteristics intended to enhance lead durability, while providing all the benefits of a thin lead. These benefits include improved ease of venous passage, reduced risk of venous thrombosis or rib-clavicle crush and enhanced ability to accommodate additional leads.
- **Silicone Tip***
 - The Durata lead's soft silicone tip offers more compliance at the lead tip-endocardium interface. This silicone tip profile has been increased by more than 60% over predecessor leads, but still passes through a 7 F introducer due to the material's soft nature. In addition, four pads have been added to the silicone tip, further increasing the surface area of the lead tip that is in contact with the tissue.
- **Slightly Curved RV Shock Coil**
 - The RV shock coil for the Durata defibrillation lead is slightly curved to help reduce pressure at the lead tip-endocardium interface.
- **Easier Implants with Fast-Pass® Coating**
 - The Durata defibrillation leads feature a lubricious coating that facilitates lead insertion through the introducer and veins. Fast-Pass coating helps reduce lead body surface friction allowing multiple leads to easily move against one another and reducing the chance of inadvertently moving one lead during the manipulation of another.
- **Shock Coil Spacing Options to Fit Most Patients**
 - Two different tip-to-proximal shock coil spacing options are available in the Durata lead. These options help promote an effective shocking vector by allowing proper positioning of the proximal coil across a wide range of cardiac shapes and sizes.
- **Shock Coil Configuration Options with Dual- or Single-Shock Coil Models***
 - The Durata defibrillation lead is available in both dual- and single-shock coil configurations, giving physicians the option to choose the configuration that is best for each patient.
- **Multiple Lengths**
 - Available in 60, 65 and 75 cm lengths, the Durata defibrillation lead affords physicians the flexibility to address the needs of patients with varying physical statures and vascular anatomies.
- **More Sensing Options with True or Integrated Bipolar Sensing***
 - The Durata defibrillation lead provides physicians the option of integrated or true bipolar sensing. The integrated bipolar sensing configurations may help improve the consistency of R-wave amplitudes and the sensing of small R waves.
- **Limited Lifetime Warranty.**
 - Terms and Conditions Apply. Refer to the Warranty for Details.

* Active fixation models only.



ST. JUDE MEDICAL™
MORE CONTROL. LESS RISK.

Durata® True Bipolar, Active-Fixation Defibrillation Leads

SPECIFICATIONS

LEAD MODEL NUMBER	7120	7121	7122
Fixation	Ext/Ret Helix	Ext/Ret Helix	Ext/Ret Helix
Shock Configuration	Dual-Coil	Dual-Coil	Single-Coil
Sensing Configuration	True Bipolar	True Bipolar	True Bipolar
Min. Size Introducer	7 F	7 F	7 F
Lengths	60, 65 cm	60, 65, 75 cm	60, 65 cm
Body Diameter	6.8 F	6.8 F	6.8 F
Tip-to-Anode Spacing	11 mm	11 mm	11 mm
Tip-to-Proximal Coil	17 cm	21 cm	N/A
Tip Electrode Area	8 mm ²	8 mm ²	8 mm ²
Steroid Plug	Yes	Yes	Yes
Distal Shock Coil Area	367 mm ²	367 mm ²	367 mm ²
Proximal Shock Coil Area	588 mm ²	588 mm ²	N/A

Durata® Integrated Bipolar, Active-Fixation Defibrillation Leads

SPECIFICATIONS

LEAD MODEL NUMBER	7130	7131
Fixation	Ext/Ret Helix	Ext/Ret Helix
Shock Configuration	Dual-Coil	Dual-Coil
Sensing Configuration	Integrated Bipolar	Integrated Bipolar
Min. Size Introducer	7 F	7 F
Lengths	60 and 65 cm	60 and 65 cm
Body Diameter	6.8 F	6.8 F
Tip-to-Distal Coil Spacing	11 mm	11 mm
Tip-to-Proximal Coil	17 cm	21 cm
Tip Electrode Area	8 mm ²	8 mm ²
Steroid Plug	Yes	Yes
Distal Shock Coil Area	367 mm ²	367 mm ²
Proximal Shock Coil Area	588 mm ²	588 mm ²

Durata® True Bipolar, Passive-Fixation Defibrillation Leads

SPECIFICATIONS

LEAD MODEL NUMBER	7170	7171
Fixation	Tines	Tines
Shock Configuration	Dual-Coil	Dual-Coil
Sensing Configuration	True Bipolar	True Bipolar
Min. Size Introducer	7 F	7 F
Lengths	60, 65 cm	65, 75 cm
Body Diameter	6.8 F	6.8 F
Tip-to-Anode Spacing	11 mm	11 mm
Tip-to-Proximal Coil	17 cm	21 cm
Tip Electrode Area	3.5 mm ²	3.5 mm ²
Steroid Plug	Yes	Yes
Distal Shock Coil Area	367 mm ²	367 mm ²
Proximal Shock Coil Area	588 mm ²	588 mm ²

ATRIAL FIBRILLATION

CARDIAC RHYTHM MANAGEMENT

CARDIAC SURGERY

CARDIOLOGY

NEUROMODULATION

St. Jude Medical

Cardiac Rhythm
Management Division
15900 Valley View Court
Sylmar CA 91342
USA
+1 818 362 6822
+1 818 364 5814 Fax

St. Jude Medical Sweden AB

Veddestavägen 19
175 84 Järfälla
Sweden
+46 8 474 4000
+46 8 760 9542 Fax

St. Jude Medical Europe, Inc.

The Corporate Village
Figueras Building
Avenue Da Vinci laan, 11 Box F1
B-1935 Zaventem
Belgium
+32 2 774 6811
+32 2 772 8384 Fax

St. Jude Medical

World Headquarters
One Lillehei Plaza
St. Paul MN 55117
USA
+1 651 483 2000
+1 651 482 8318 Fax

sjm.com



ST. JUDE MEDICAL™
MORE CONTROL. LESS RISK.

CAUTION: FEDERAL LAW (USA) RESTRICTS THIS DEVICE TO SALE, DISTRIBUTION AND USE BY OR ON THE ORDER OF A PHYSICIAN. Consult the User's Manual for information on indications, contraindications, warnings and precautions. Unless otherwise noted, ® or ™ indicates that the name is a trademark of, or licensed to, St. Jude Medical, or one of its subsidiaries. ST. JUDE MEDICAL, the nine-squares symbol and MORE CONTROL. LESS RISK. are trademarks and service marks of St. Jude Medical, Inc. and its related companies. ©2009 St. Jude Medical, Inc. All Rights Reserved. Item No. G0210